

P range generators

The **P** range offers high performance, robust design and simple maintenance. This range is ideal for construction, livestock farming, and agriculture, to name just a few industries. These products have been designed at our innovation center to guarantee the highest quality standards.

P 3000 W



Key features

- Recoil start
- Large fuel tank
- Sockets
- Automatic Voltage Regulation (AVR)
- Hour meter
- Circuit breaker
- Low oil level protection

**P 6500 W
P 8000 W**



Key features

- Recoil start
- Electric key start (12V)
- Large fuel tank
- Sockets
- Automatic Voltage Regulation (AVR)
- Hour meter Circuit breaker
- Wheel kit
- Low oil level protection



Technical data

Generator data		P3000W	P6500W	P8000W
Rated frequency	Hz	60	60	60
Rated voltage	V	240 / 120	240 / 120	240 / 120
Nominal power output	kVA	2,5	5,0	6,5
Peak power output	kVA	2,8	5,5	7,0
Power factor cos Phi		1	1	1
Fuel tank capacity	gal	4	6,6	6,6
Fuel autonomy at nominal power	hr	11	10	8
Sockets configuration		1 x 120V Duplex 15A + 1 x 120/240V 30ATwist lock	2 x 120V Duplex 15A + 1 x 120/240V 30ATwist lock	2 x 120V Duplex 15A + 1 x 120/240V 30ATwist lock
Engine				
Model		AC200FA Gasoline	AC390FD Gasoline	AC420FD Gasoline
Nominal speed	rpm	3600	3600	3600
Power output	kWm	4,1	8,2	9
Displacement	cm ³	196	389	420
Starter type		Recoil	Electric / Recoil	Electric / Recoil
Exhaust gas compliant		EPA Tier 2	EPA Tier 2	EPA Tier 2
Alternator				
Power	kVA	2,5	5,5	6,5
Noise level				
Sound pressure level (LpA) at 7m	dB(A)	73	75	76
Sound power level (LwA)	dB(A)	95	97	101
Weight and dimensions				
Length	inches	23 1/4"	26 5/8"	26 3/4"
Width	inches	17"	21 1/4"	21 5/8"
Height	inches	19"	21 1/4"	21 5/8"
Weight	lbs	115	174	183